


At a Glance

Applications



- › ELSR-H
- › ELSR-SHH

Benefits

- › Cold connection technology
- › Simple and quick assembly


Approvals



- › Classification
 - II 2G Ex db IIC Gb
 - II 1D Ex ta IIC Da
- › Certification
 - CML 19 ATEX 1346 X
 - IECEX CML 19.0104 X

ELVB-SRAH-Ex-20

ELSR - Connection set



The Cold connection technology is the ideal solution for simple and quick connection of the ELSR heating cable to a suitable junction box.

Checklist

No.	Type	Quantity
1	Cable gland M20 x 1,5; Brass, with UNI gasket	1 Pcs.
2	Heat shrink Ø = 3/16" (4,8 mm); 180 mm long; green/yellow	1 Pcs.
3	Isolator for ELSR-connection; Silicone	1 Pcs.
4	Pin terminal 4-6 mm ² ; E-Cu galvanically tin-plated	1 Pcs.
5	Pin terminal 1,5-2,5 mm ² ; E-Cu galvanically tin-plated	1 Pcs.
6	Wire end sleeves 1,5 mm ² ; black	2 Pcs.
7	Silicone glue; „ECH“ red, 5 gr	1 Pcs.

Technical Information

Operating temperature	-60 °C up to +180 °C (7 Joule)
Protection according EN 60529	IP 64*
UV-Resistance	Yes

*An IP washer can be ordered separately to achieve IP66/68 (50m 7 days) ingress protection rating.

Order information

Type	Art.-No.
ELVB-SRAH-Ex-20	0X81PHD
IP-washer, M20, PTFE, -200°C to +260°C	2578020000