


At a Glance

Applications



› ELP/PFA

Benefits

- › Cold connection technology
- › Simple and quick assembly


Approvals



- › Classification
 - II 2G Ex db IIC Gb
 - II 1D Ex ta IIC Da
- › Certification
 - CML 19 ATEX 1346 X
 - IECEx CML 19.0104 X

ELVB-ELPEX-20

ELP - Connection set



The Cold connection technology is the ideal solution for simple and quick connection of the ELP heating cable to a suitable junction box.

Checklist

No.	Type	Quantity
1	Cable gland M20 x 1,5; Brass, with UNI gasket	1 Pcs.
2	Heat shrink Ø = 3/16" (4,8 mm); 120 mm long; green/yellow	1 Pcs.
3	Silicone tube Ø = 4 mm; 30 mm long; natural	1 Pcs.
4	Pin terminal lug 1.5-2.5 mm ² ; E-Cu galvanic tinned	1 Pcs.
5	Ferrules 1.5 mm ² ; black	2 Pcs.

Technical Information

Operating temperature	-60 °C up to +180 °C (7 Joule)
Protection according EN 60529	IP 64*
UV-Resistance	Yes

*An IP washer can be ordered separately to achieve IP66/68 (50m 7 days) ingress protection rating.

Order information

Type	Art.-No.
ELVB-ELPEX-20	0X81PPD
IP-washer, M20, PTFE, -200°C to +260°C	2578020000