

At a Glance


Applications




Pipelines

ELB Type 13 & ELB Type 15


Pipe- and hose fastening



ELB-13V2



ELB-13V1



ELB-15

Self-assembly clamp

Type:	ELB-13V1	ELB-13V2
Material:	1.4301	1.4301
Closure type:	Turnbuckle (ELB-13V2)	Screw connection with external hexagon and slot
Packaging unit:	30 m per roll	100 units
Tensions band width	11 mm	
Profile:	Perforated	

Hose clamps W4 / 1.4301

Standard:	DIN 3017										
Material:	W4 / 1.4301										
Surface finish:	Blank										
Type & clamping area:	<table> <tr> <td>ELB-15.02</td><td>Ø 16 up to 25 mm, up to DN 15, 1/2"</td></tr> <tr> <td>ELB-15.04</td><td>Ø 25 up to 40 mm, up to DN 25, 1"</td></tr> <tr> <td>ELB-15.06</td><td>Ø 40 up to 60 mm, up to DN 40, 1,5"</td></tr> <tr> <td>ELB-15.110</td><td>Ø 60 up to 110 mm, up to DN 80, 3"</td></tr> <tr> <td>ELB-15.11</td><td>Ø 90 up to 110 mm, up to DN 80, 3"</td></tr> </table>	ELB-15.02	Ø 16 up to 25 mm, up to DN 15, 1/2"	ELB-15.04	Ø 25 up to 40 mm, up to DN 25, 1"	ELB-15.06	Ø 40 up to 60 mm, up to DN 40, 1,5"	ELB-15.110	Ø 60 up to 110 mm, up to DN 80, 3"	ELB-15.11	Ø 90 up to 110 mm, up to DN 80, 3"
ELB-15.02	Ø 16 up to 25 mm, up to DN 15, 1/2"										
ELB-15.04	Ø 25 up to 40 mm, up to DN 25, 1"										
ELB-15.06	Ø 40 up to 60 mm, up to DN 40, 1,5"										
ELB-15.110	Ø 60 up to 110 mm, up to DN 80, 3"										
ELB-15.11	Ø 90 up to 110 mm, up to DN 80, 3"										
Band width:	12 mm										
Closure type:	Screw connection with external hexagon and slot										
Width across flats:	WAF 7										
Tightening torque:	5 Nm										
Required tools:	Wrench WAF 7 or Slotted screwdriver										

Hose clamps W2 / 1.4016

Standard:	DIN 3017
Material:	W2 / 1.4016
Surface finish:	Blank
Type & clamping area:	ELB-15.090 Ø 40 up to 90 mm, up to DN 65, 2,5" ELB-15.09 Ø 70 up to 90 mm, up to DN 65, 2,5" ELB-15.325 Ø 60 up to 325 mm, up to DN 250, 10" ELB-15.650 Ø 60 up to 650 mm, up to DN 600, 24"
Band width	9 mm
Closure type:	Quick-release screw connection with external hexagon and slot
Width across flats:	WAF 7
Tightening torque:	5 Nm
Required tools:	Wrench WAF 7 or Slotted screwdriver

Ordering Information

Type	Description	Item No.
ELB-13V1	Threaded tensioning strap; Perforated, 30 m, 11 mm, Mat. 1.4301	2723001010
ELB-13V2	Turnbuckle; Mat. 1.4301, Packaging unit = 10 units	0930042
ELB-15.02	Hose clamp ELB-15.02; 16 up to 25 mm, up to DN 15, 1/2", Mat. 1.4301	2723001016
ELB-15.04	Hose clamp ELB-15.04; 25 up to 40 mm, up to DN 25, 1", Mat. 1.4301	2723001025
ELB-15.06	Hose clamp ELB-15.06, 40 up to 60 mm, up to DN 40, 1,5", Mat. 1.4301	2723001040
ELB-15.110	Hose clamp ELB-15.110; 60 up to 110 mm, up to DN 80, 3", Mat. 1.4301	2723050110
ELB-15.11	Hose clamp ELB-15.11; 90 up to 110 mm, up to DN 80, 3", Mat. 1.4301	2723001090
ELB-15.090	Hose clamp ELB-15.090; 40 up to 90 mm, up to DN 65, 2,5", Mat. 1.4016	2723040090
ELB-15.09	Hose clamp ELB-15.09, 70 up to 90 mm, up to DN 65, 2,5", Mat. 1.4016	2723001071
ELB-15.325	Hose clamp ELB-15.325; 60 up to 325 mm, up to DN 250, 10", Mat. 1.4016	2723060325
ELB-15.650	Hose clamp ELB-15.090; 60 up to 650 mm, up to DN 600, 24", Mat. 1.4016	2723060650