

At a Glance


Applications




Pipelines

ELB-16 & ELB-25

Cable tie



ELB-16



ELB-25

Cable tie PA ELB-16

Operating temperature:	-40 °C up to 85 °C
Material:	Polyamide, black UV-resistant, Silicone-free, Halogen-free
Dimensions:	102 x 2,5 mm (ELB-16.10) 200 x 3,6 mm (ELB-16.20) 360 x 4,8 mm (ELB-16.36)
Packaging unit:	100 units

Cable tie VA ELB-25

Operating temperature:	-80 °C up to 538 °C
Material:	1.4401, White-silver
Dimensions:	100 x 4,6 mm (ELB-25.01) 360 x 7,9 mm (ELB-25.02) 680 x 7,9 mm (ELB-25.03) 1400 x 7,9 mm (ELB-25.04)
Packaging unit:	10 units

Ordering Information

Type	Description	Item No.
ELB-16.10	Cable tie 102 x 2,5 mm; PA, 100 units	2796000001
ELB-16.20	Cable tie 200 x 3,6 mm; PA, 100 units	2796000002
ELB-16.36	Cable tie 360 x 4,8 mm; PA, 100 units	2796000003
ELB-25.01	Cable tie 100 x 4,6 mm; VA, 10 units	0942301
ELB-25.02	Cable tie 360 x 7,9 mm; VA, 10 units	0942302
ELB-25.03	Cable tie 680 x 7,9 mm; VA, 10 units	0942303
ELB-25.04	Cable tie 1400 x 7,9 mm; VA, 10 units	0942304