(1) # EU - Type Examination Certificate

(2) Equipment and protective systems intended for use in potentially explosive atmospheres – **Directive 2014/34/EU**

(3) EU - Type Examination Certificate Number

EPS 19 ATEX 1 014 X **Revision 1**

(4) Equipment: Heating cable system ELSR-N-Ex

(5) Manufacturer: eltherm production GmbH

(6) Address: Ernst-Heinkel-Straße 6-10
57299 Burbach
Germany

(7) This equipment and any acceptable variation thereto are specified in the annex to this certificate and the documentation therein referred to.

(8) Bureau Veritas Consumer Products Services Germany GmbH, notified body No. 2004 in accordance with Article 21 given in the Directive 2014/34/EU of the European Parliament and of the Council of 26 February 2014, certifies that this equipment has been found to comply with the essential health and safety requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres, given in Annex II of the Directive. The examination and test results are recorded in the confidential documentation under the reference number 19TH0131_01.

(9) Compliance with the essential health and safety requirements has been assured by compliance with:

EN IEC 60079-0:2018 **EN 60079-30-1:2017**

(10) If the sign "X" is placed after the certificate number, it indicates that the equipment is subject to special conditions of use specified in the annex to this certificate.

(11) This EU - Type Examination Certificate relates only to the design and construction of the specified equipment in accordance with Directive 2014/34/EU. Further requirements of this Directive apply to the manufacture of this equipment and its placing on the market. Those requirements are not covered by this certificate.

(12) The marking of the equipment shall include the following:

II 2G Ex 60079-30-1 IIC T6 Gb

II 2D Ex 60079-30-1 IIIC T85°C Db



Certification department of explosion protection

Tuerkheim, 2026-03-20

ppa.

Certifier

Certificates without signature and seal are void. This certificate is allowed to be distributed only if not modified. Extracts or modifications must be authorized by Bureau Veritas Consumer Products Services Germany GmbH.

(13) # Annex

(14) **EU - Type Examination Certificate EPS 19 ATEX 1 014 X** **Revision 1**

(15) Description of equipment:

The heating cable system ELSR-N-Ex consists of ATEX-approved components and is suitable for use on pipes, vessels and associated equipment in areas with combustible gas or dust (Equipment Group II, Equipment Protection Level Gb and Db for T-Class T6 or T85 °C).

The system assembly consists of:

Self-regulating heating cable ELSR-N-... with power 10, 20, 30 and 40 W/m at 10 °C	(EPS 18 ATEX 1 133 U)
Cable gland M25x1.5	(IBExU07ATEX1022X)
Cable gland EL-GSR	(IBExU25ATEX1041X)
Ex d cable gland Peppers A8**	(CML19ATEX1346X)
End cap EL-ECN	(EPS 19 ATEX 1 012 U)
Cable Joint Ex-Con SR	(IBExU07ATEX1080X)
Mounting assembly	(IBExU09ATEX1023U)

Electrical data:

Voltage: 230 / 277 V AC

Power: 10, 20, 30 and 40 W/m

(16) Reference number: 19TH0131_01

(17) Special conditions of use:

Application temperature, depending on system components: max. -60 °C to +80 °C

When determining the limit temperature, the operating temperature ranges for the system components that have direct contact with heated equipment must be considered.

Heating cable ELSR-N	-60 °C to +80 °C
Cable gland M25x1.5	-25 °C to +70 °C (7J)
	-55 °C to +70 °C (4J)
Cable gland EL-GSR	-60 °C to +130 °C
Ex d cable gland Peppers A8**	-60 °C to +180 °C
End cap EL-ECN	-60 °C to +135 °C
Connection sleeve Ex-Con SR	-32 °C to +200 °C
Mounting foot Ex-It	-20 °C to +200 °C

At temperatures below -25 °C, the gland M25x1.5 shall be protected against mechanical stress.

The Ex-Con SR cable joint shall be installed to protect it from mechanical stress.

The system components shall be combined so that all free ends of the heating cable are closed or contacted.

Installation and commissioning shall only be carried out by trained specialist personnel in accordance with the requirements of EN 60079-14, Annex F and in accordance with the manufacturer's specifications.

The free cable ends are to be connected to separate junction boxes (which are approved according to a recognized type of protection) via the system cable gland or to the system junction boxes type ELAK-Ex-R via the system mounting assembly Ex-It.

EU - Type Examination Certificate EPS 19 ATEX 1 014 X **Revision 1**

(18) Essential health and safety requirements:

Met by compliance with standards.

Certification department of explosion protection Tuerkheim, 2026-03-20

Certifier